

PRODUCT DATA SHEET



UREKA®

Ueroplast-55

PRODUCT DISCRIPTION

Ueroplast-55 is a high-quality, ready-mix dry plaster designed for interior and exterior wall applications. This product provides a smooth, durable finish that is ideal for a variety of surfaces, including concrete, brickwork, and blockwork. Ueroplast-55 is formulated for easy application, excellent workability, and quick setting, making it a perfect choice for both new construction and renovation projects.

FEATURES & BENEFITS

- Ready-mix formula for quick and easy application
- High bonding strength
- Suitable for both interior and exterior use
- Provides a smooth and durable finish
- Excellent workability and easy to apply
- Reduced cracking and shrinkage

Applications

- Interior and exterior wall plastering
- Suitable for application on concrete, brickwork, and blockwork
- Ideal for use in residential, commercial, and industrial buildings

Technical Data

Appearance	Grey powder
Mixing Ratio	Approximately 7.5-8.5 liters of water per 25 kg bag
Pot Life	Pot Life
Setting Time	Initial set in 60-90 minutes, final set in 3-4 hours
Compressive Strength	≥ 7.5 MPa after 28 days
Coverage	Approximately 1.5-2.0 kg/m ² per mm of thickness (depending on substrate and application thickness)
Layer Thickness	10-15 mm in a single application
Shelf Life	06 months in unopened bags, stored in a dry place

Application Instructions

- **Surface Preparation:** Ensure the surface is clean, dry, and free from dust, grease, and loose particles. Dampen highly absorbent surfaces before application.
- **Mixing:** Gradually add Ueroplast-55 to the recommended amount of clean water while mixing to a smooth, lump-free consistency
- **Application:** Apply the mixed plaster to the surface using a trowel. For best results, apply in layers of 10-15 mm thickness. Use a straight edge to level the surface and achieve the desired finish.
- **Curing:** Allow the plaster to dry naturally. Avoid rapid drying by protecting the applied plaster from direct sunlight, strong winds, and excessive heat.

Packaging

- Available in 25 kg bags

Storage

- Store in a cool, dry place, away from direct sunlight. Keep the bags tightly sealed when not in use.

Health & Safety

- Wear protective gloves and eyewear during handling and application.
- In case of contact with skin or eyes, rinse immediately with plenty of water and seek medical advice if irritation persists.
- Keep out of reach of children.

Disposal

- Dispose of contents and packaging in accordance with local regulations.